

# DATA SHIEFT

#### Lens Part No: OPLLC0011

LED: LUMILED LUXEON 2835



www.opticsindia.com





## **Contents**

- 1. Lens Details, Usage & Maintenance
- 2. LED Source Details
- 3. Simulation Tool Details
- 4. Plots and Results
- 5. Lens Drawing And Package Specification
- 6. Contact Details

www.opticsindia.com







### Lens Details, Usage & Maintenance

SL.No	Parameter	Specification
1.	Lens Material	РММА
2.	Lens Dimensions	Ø 19.40 mm & Height 13.50 mm
3.	Operating Temperature $(T_{Opt})$	-40 to $+80^{\circ}$ C
4.	Lighting Application	Flood Light and Bay Light

1. If necessary, clean Lenses with mild soap, water and soft cloth.

2. Never use any commercial cleaning solvents on Lenses, like alcohol.

3. Please handle or install Lenses with wearing gloves, skin oil may damage Lens or its Optical Characteristic.

Note: Simulation carried out by coupling single Lens with LUMILED LUXEON 2835 LED.

www.opticsindia.com



#### **LED Source Details**

SL.No	Parameter	Specification
1.	Lamp	LUXEON 2835
2.	LED Manufacture	LUMILED
3.	LED Forward Current	150 mA
4.	LED Forward Voltage	9.1 V
5.	LED Viewing Angle	1200
6.	Number of Sources	1
7.	Simulation Tool	Trace-Pro

#### **Simulation Tool : Trace-Pro**

Trace-Pro is Award-Winning Opto-Mechanical software developed by 'Lamda Research Corporation'USA, under SBIR grant from NASA.


It combines design, ray tracing, analysis, optimization methods to solve a wide variety of new problems in illumination design.


It provides advanced tools for designing medical devices, illumination, display back lights, light pipes, automotive lighting and many other applications.



#### **Plots and Results**

#### **Intensity Distribution Plots:**





Polar Candela Distribution

S. No	Parameter	Beam Angle
1.	FWHM Angle	37.81
2.	FWTM Angle	64.78
3.	Efficiency	93%
4.	cd/lm	2.0

#### Note:


**FWHM angle -**Full Width Half Maximum angle (Beam angle at 50% of the maximum Intensity)

**FWTM angle -** Full Width Tenth Maximum angle (Beam angle at 10% of the maximum Intensity)

www.opticsindia.com

## **Lens Drawing:**





6

#### "We Are Ready To Lead You Into The Future Of Optics"

- Our Components of high efficiency, are easy to mount and compact in size.
- Any flow lines on the external surface of the lens are acceptable if the optical characteristics are not affected.
- We are incredibly responsive to your requests and value your questions.



#### GET IN TOUCH WITH US

Optics & Allied Engg. Pvt. Ltd. No. 9Q, 1st Phase, Jigani Link Road, Bommasandra Industrial Area, Bangalore-560099, INDIA Tel: +91-80-41134421 Email: sales@opticsindia.com

www.opticsindia.com