


DATA SHIEET

Lens Part No: OPLLC0050

LED: NICHIA NVSW319B








Contents

- 1. Lens Details, Usage & Maintenance
- 2. LED Source Details
- 3. Simulation Tool Details
- 4. Plots and Results
- 5. Lens Drawing And Package Specification
- 6. Contact Details





Lens Details, Usage & Maintenance

SL.No	Parameter	Specification
1.	Lens Material	PMMA
2.	Lens Dimensions	Ø 14.76 mm & Height 8.30 mm
3.	Holder Dimensions	Ø 16.20 mm & Height 9.80 mm
4.	Operating Temperature (T_{Opt})	-40 to +80° C
5.	Lighting Application	Flood Light and Bay Light

- 1. If necessary, clean Lenses with mild soap, water and soft cloth.
- 2. Never use any commercial cleaning solvents on Lenses, like alcohol.
- 3. Please handle or install Lenses with wearing gloves, skin oil may damage Lens or its Optical Characteristic.

Note: Simulation carried out by coupling single Lens with NICHIA NVSW319B LED.



LED Source Details

SL.No	Parameter	Specification
1.	Lamp	NVSW319B
2.	LED Manufacture	NICHIA
3.	LED Forward Current	700 mA
4.	LED Forward Voltage	2.9 V
5.	LED Viewing Angle	1300
6.	Number of Sources	1
7.	Simulation Tool	Trace-Pro

Simulation Tool: Trace-Pro

Trace-Pro is Award-Winning Opto-Mechanical software developed by 'Lamda Research Corporation'USA, under SBIR grant from NASA.


It combines design, ray tracing, analysis, optimization methods to solve a wide variety of new problems in illumination design.


It provides advanced tools for designing medical devices, illumination, display back lights, light pipes, automotive lighting and many other applications.



Plots and Results

Intensity Distribution Plots:





S. No	Parameter	Beam Angle
1.	FWHM Angle	22.47
2.	FWTM Angle	35.37
3.	Efficiency	92%
4.	cd/lm	5.8

Note:

FWHM angle -Full Width Half Maximum angle (Beam angle at 50% of the maximum Intensity)


FWTM angle - Full Width Tenth Maximum angle (Beam angle at 10% of the maximum Intensity)

Lens Drawing: 252.0 ķ RETISSEN RESIDERED 02.30 13.40 *05.8 www.opticsindia.com OPLLC0050

6

Holder Drawing:





"We Are Ready To Lead You Into The Future Of Optics"

- Our Components of high efficiency, are easy to mount and compact in size.
- ❖ Any flow lines on the external surface of the lens are acceptable if the optical characteristics are not affected.
- ❖ We are incredibly responsive to your requests and value your questions.



GET IN TOUCH WITH US

Optics & Allied Engg. Pvt. Ltd.

No. 9Q, 1st Phase, Jigani Link Road, Bommasandra Industrial Area, Bangalore-560099, INDIA

Tel: +91-80-41134421

Email: sales@opticsindia.com