

DATA SHIEET

Lens Part No: OPLLS0126C

LED: OSRAM OSLON SQUARE







Contents

- 1. Lens Details, Usage & Maintenance
- 2. LED Source Details
- 3. Simulation Tool Details
- 4. Plots and Results
- 5. Lens Drawing And Package Specification
- 6. Contact Details





Lens Details, Usage & Maintenance

SL.No	Parameter	Specification
1.	Lens Material	Polycarbonate
2.	Lens Dimensions ($L \times W \times H$)	70 x 60 x 660mm
3.	Operating Temperature (T_{Opt})	-40 to +120° C
4.	Lighting Application	Street Light

- 1. If necessary, clean Lenses with mild soap, water and soft cloth.
- 2. Never use any commercial cleaning solvents on Lenses, like alcohol.
- 3. Please handle or install Lenses with wearing gloves, skin oil may damage Lens or its Optical Characteristic.

Note: Simulation carried out by coupling 9 in 1 street light lens with OSRAM OSLON SQUARE LED.



LED Source Details

SL.No	Parameter	Specification
1.	Lamp	OSLON SQUARE
2.	LED Manufacture	OSRAM
3.	LED Forward Current	700 mA
4.	LED Forward Voltage	2.8 V
5.	LED Viewing Angle	1200
6.	Number of Sources	9
7.	Simulation Tool	Trace-Pro

Simulation Tool: Trace-Pro

Trace-Pro is Award-Winning Opto-Mechanical software developed by 'Lamda Research Corporation'USA, under SBIR grant from NASA.


It combines design, ray tracing, analysis, optimization methods to solve a wide variety of new problems in illumination design.


It provides advanced tools for designing medical devices, illumination, display back lights, light pipes, automotive lighting and many other applications.



Plots and Results

Intensity Distribution Plots:





S. No	Parameter	Spread	Throw
1.	FWHM Angle	142°	52°
2.	FWTM Angle	159°	114°
3.	Efficiency	90%	
4.	cd/lm	0.70	


Note:

FWHM angle -Full Width Half Maximum angle (Beam angle at 50% of the maximum Intensity)

FWTM angle - Full Width Tenth Maximum angle (Beam angle at 10% of the maximum Intensity)



Roadway Classification:




Roadway Analysis:

BOOM ANGLE	DISTRIBUTION TYPE
0 °	II SHORT
5°	II SHORT
10°	II SHORT
15°	III SHORT

Lens Drawing:





"We Are Ready To Lead You Into The Future Of Optics"

- Our Components of high efficiency, are easy to mount and compact in size.
- ❖ Any flow lines on the external surface of the lens are acceptable if the optical characteristics are not affected.
- ❖ We are incredibly responsive to your requests and value your questions.



GET IN TOUCH WITH US

Optics & Allied Engg. Pvt. Ltd.

No. 9Q, 1st Phase, Jigani Link Road, Bommasandra Industrial Area, Bangalore-560099, INDIA

Tel: +91-80-4113 4421

Email: sales@opticsindia.com